

Please type a plus sign (+) inside this box → ☐

PTO/SB/05 (12/97)
Approved for use through 09/30/00. OMB 0651-0032
Patent and Trademark Office: U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

UTILITY PATENT APPLICATION TRANSMITTAL (Only for new nonprovisional applications under 37 CFR 1.53(b))	Attorney Docket No.	Total Pages
	First Named Inventor or Application Identifier Takahisa Ueda	
	Express Mail Label No.	

APPLICATION ELEMENTS See MPEP chapter 608 concerning utility patent application contents.	ADDRESS TO: Assistant Commissioner for Patents Box Patent Application Washington, DC 20231
---	---

1. <input type="checkbox"/> Fee Transmittal Form (Submit an original, and a duplicate for fee processing)	6. <input type="checkbox"/> Microfiche Computer Program (Appendix)
2. <input checked="" type="checkbox"/> Specification [Total Pages 46] (preferred arrangement set forth below) <ul style="list-style-type: none">- Descriptive title of the invention- Cross References to Related Applications- Statement Regarding Fed sponsored R & D- Reference to Microfiche Appendix- Background of the invention- Brief Summary of the invention- Brief Description of the Drawings (if filed)- Detailed Description- Claim(s)- Abstract of the Disclosure	7. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary) <ul style="list-style-type: none">a. <input type="checkbox"/> Computer Readable Copyb. <input type="checkbox"/> Paper Copy (identical to computer copy)c. <input type="checkbox"/> Statement verifying identity of above copies

3. <input checked="" type="checkbox"/> Drawing(s) (35 USC 113) [Total Sheets 14]	ACCOMPANYING APPLICATION PARTS 8. <input type="checkbox"/> Assignment Papers (cover sheet & document(s)) 9. <input type="checkbox"/> 37 CFR 3.73(b) Statement [] Power of Attorney (when there is an assignee) 10. <input type="checkbox"/> English Translation Document (if applicable) 11. <input type="checkbox"/> Information Disclosure [] Copies of IDS Statement (IDS)/PTO-1449 Citations 12. <input type="checkbox"/> Preliminary Amendment 13. <input checked="" type="checkbox"/> Return Receipt Postcard (MPEP 503) (Should be specifically itemized) 14. <input type="checkbox"/> Small Entity [] Statement filed in prior application, Statement(s) Status still proper and desired 15. <input type="checkbox"/> Certified Copy of Priority Document(s) (if foreign priority is claimed) 16. <input checked="" type="checkbox"/> Other: copy of Submission under 37 CFR 1.125 copy of LETTER TO OFFICIAL DRAFTSMAN
4. Oath or Declaration [Total Pages 3] <ul style="list-style-type: none">a. <input type="checkbox"/> Newly executed (original or copy)b. <input checked="" type="checkbox"/> Copy from a prior application (37 CFR 1.63(d)) (for continuation/divisional with Box 17 completed) (Note Box 6 below)<ul style="list-style-type: none">i. <input type="checkbox"/> DELETION OF INVENTOR(S) Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).	
5. <input type="checkbox"/> Incorporation By Reference (useable if Box 4b is checked) The entire disclosure of the prior application, from which a copy of the oath or declaration is supplied under Box 4b, is considered as being part of the disclosure of the accompanying application and is hereby incorporated by reference therein.	
17. If a CONTINUING APPLICATION, check appropriate box and supply the requisite information: <input type="checkbox"/> Continuation <input checked="" type="checkbox"/> Divisional <input type="checkbox"/> Continuation-in-part (CIP) of prior application No: 09 1048, 251*	

18. CORRESPONDENCE ADDRESS	
<input type="checkbox"/> Customer Number or Bar Code Label	or <input type="checkbox"/> Correspondence address below

(Insert Customer No. or Attach bar code label here)					
NAME	Felix J. D'Ambrasio				
ADDRESS	P.O. Box 2266 Eads Station				
CITY	Arlington	STATE	VA	ZIP CODE	22202
COUNTRY	U.S.A.	TELEPHONE	(703) 415-1500	FAX	(703) 415-1508

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

* which is a Divisional Application of Application No. 08/549,783

Specification

Gland Packing

5 Technical Field

The present invention relates to a gland packing which is useful as a shaft seal device for a hydraulic machine such as a valve or a pump, and more particularly to a gland packing which is charged into a stuffing
10 box and pressed by a packing gland in an axial direction so as to be brought into tight contact with the outer peripheral face of a shaft or a valve rod, thereby forming a shaft seal part.

15 Background Art

As such a gland packing, conventionally, known is a die mold packing 51 having a usual structure shown in Fig. 25. The die mold packing 51 is configured by
windingly laminating a tape-like material 50 such as an
20 expanded graphite tape into a spiral shape, and then die-molding the lamination into a ring-like shape. Such a die mold packing 51 is used in the following manner. As shown in Fig. 26, in a stuffing box 54, the die mold packings 51, and a plurality of laminate packings 53
25 which are obtained by laminating ring-like sheet mate-

rials 52 having impermeability are alternately disposed on the outer periphery of a shaft or a valve rod 55 (hereinafter, referred to as "valve rod or the like") in an axial direction. Alternatively, as shown in Fig. 5 27, the die mold packings 51, and braided packings 56 which are well known in the art are combinedly disposed. These packings are pressed in the axial direction through a packing gland 57 so that their inner peripheral face parts are brought into tight contact 10 with the outer peripheral face of the valve rod or the like 55, thereby performing the shaft sealing operation.

Furthermore, also a gland packing 58 is known in which, as shown in Fig. 28, a ring-like projected part 15 51a is formed on an end face in an axial direction of the die mold packing 51 and in an outer end portion in a radial direction so that the ring-like projected part is projected outward in the axial direction, and a ring-like recess 56a which is formed on an end face in 20 the axial direction of the braided packings 56 and in an outer end portion in a radial direction is fitted onto the ring-like projected part 51a, thereby integrating the packings 51 and 56 into one body. Also the integrated gland packing 58 is used in the following 25 manner. As shown in Fig. 29, the integrated gland

packings 58 are combinedly disposed in the stuffing box 54 together with the die mold packings 51 having the ring-like projected part 51a. In the same manner as described above, these packings are pressed in an axial direction through the packing gland 57 so that their inner peripheral face parts are brought into tight contact with the outer peripheral face of the valve rod or the like 55, thereby performing the shaft sealing operation.

10 In a prior art gland packing mainly consisting of the die mold packings 51, as shown in Figs. 25 and 28, minute gaps 59 are inevitably formed in windingly laminated parts of the tape-like material 50. A pressurized fluid penetrates into the minute gaps 59, and leakage indicated by the arrow a easily occurs. Partic- 15 ularly when a gas fluid of low molecular weight flows through the hydraulic machine, it is very difficult to prevent penetration leakage from occurring.

Furthermore, the die mold packing 51 which is 20 configured by windingly laminating the tape-like material 50 has originally a lower strength. In a use manner, the die mold packing is disposed in substantially parallel to the axis of the valve rod or the like 55. When the material is pressed in an axial 25 direction, the material is swollen out to enter the

gaps so that stress relaxation easily occurs. Furthermore, the process of the die molding is conducted at a high face pressure. When the die mold has a rectangular section shape, therefore, the die mold cannot exhibit
5 sufficient sealing performance at a low tightening force.

Moreover, when the die mold packings 51 and the laminate packings 53 are combinedly used as shown in Fig. 26, the amount of deformation of the laminate
10 packings 53 in the pressurizing process is small, and hence the laminate packings 53 must be produced with very high dimensional accuracy. Furthermore, the parts of the laminate packings 53 are easily worn. Even when the parts are worn at a very small amount, the contact
15 surface pressure acting on the valve rod or the like 55 is extremely lowered, thereby producing a problem in that sealing performance is largely impaired.

The invention has been conducted in view of the above-mentioned circumstances. It is an object of the
20 invention to provide a gland packing which can prevent penetration leakage from occurring, which can be sufficiently deformed so as to exhibit sure sealing properties even at a low tightening force, and which has following properties against a small amount of wear so
25 as to ensure high sealing performance for a long term.

Disclosure of the Invention

In order to attain the object, in the gland packing of the invention, a ring-like projected part which is projected outward in an axial direction is formed on
5 at least one end face in an axial direction of a die mold packing part and in at least one of outer and inner end portions in a radial direction, the die mold packing part being configured by windingly laminating an expanded graphite tape into a spiral shape and die-
10 molding the lamination into a ring-like shape, a ring-like seal member is brought into tight contact with the one end face in the axial direction of the die mold packing part excluding the ring-like projected part, and the ring-like projected part is projected in the
15 axial direction beyond an outer face of the ring-like seal member.

Alternatively, the gland packing may be configured in the following manner. The ring-like projected part is projected outward in the axial direction from the
20 both end faces in the axial direction of the die mold packing part and in the outer or inner end portion in a radial direction, or a ring-like projected part is projected from one end face in the axial direction of the die mold packing part and in the inner end portion
25 in a radial direction, and also from the other end face

in the axial direction of the die mold packing part and in the outer end portion in a radial direction so that the ring-like projected parts are projected outward in the axial direction. Ring-like seal members are respectively brought into tight contact with the end faces in the axial direction of the die mold packing part excluding the ring-like projected parts.

In the thus configured invention, a ring-like seal member is brought into tight contact with at least one of the end faces in the axial direction of the die mold packing part. Even when a pressurized fluid penetrates into minute gaps formed in windingly laminated parts of the expanded graphite tape constituting the die mold packing part, therefore, the leakage of the fluid is blocked by the ring-like seal member and stress relaxation due to the swelling out in the axial direction of the die mold packing part is suppressed by the ring-like seal member. The ring-like projected part which is projected outward in the axial direction is formed in the die mold packing part. When the gland packing is to be used while being charged in a stuffing box, therefore, the projected part is easily deformed only by applying a low tightening force in the axial direction, and hence the density of the projected part is increased and a large stress is generated in a radial

direction of the projected part so that the packing is strongly brought into tight contact with the inner face of the stuffing box and the outer peripheral face of a valve rod or the like. This surely prevents penetration
5 leakage from the projected part from occurring, and enhances sealing properties between the stuffing box and the valve rod. Furthermore, the ring-like projected part has a closely packed folded structure and is very elastic, and hence the ring-like projected part can
10 satisfactorily follow a small amount of wear, thereby ensuring penetration leak prevention and high sealing properties.

In the other gland packing of the invention, a ring-like projected part which is projected outward in
15 an axial direction is formed on at least one end face in the axial direction of a die mold packing part and in at least one of outer and inner end portions in a radial direction, the die mold packing part being configured by windingly laminating an expanded graphite
20 tape into a spiral shape and die-molding the lamination into a ring-like shape, a ring-like seal member is brought into tight contact with the one end face in the axial direction of the die mold packing part excluding the ring-like projected part, the outer face of the
25 ring-like seal member is formed as an oblique circular

cone face which is positioned more outward in the axial direction as moving toward the ring-like projected part, and the projection end face of the ring-like projected part is substantially positioned in an extension plane of the oblique circular cone face.

The gland packing may be configured so that ring-like projected parts are respectively outward projected in the axial direction from the both end faces in the axial direction of the die mold packing part and in the outer or inner end portion in a radial direction, or ring-like seal members are respectively brought into tight contact with the end faces in the axial direction of the die mold packing part excluding the ring-like projected parts.

In the thus configured gland packing, even when a pressurized fluid penetrates into minute gaps formed in windingly laminated parts of the expanded graphite tape constituting the die mold packing part, the leakage of the fluid is blocked by the ring-like seal member and stress relaxation due to the swelling out in the axial direction of the die mold packing part is suppressed by the ring-like seal member. The ring-like projected part which is projected outward in the axial direction is formed in the die mold packing part, and the projection end face of the ring-like projected part and the outer

face of the ring-like seal member are formed as an oblique circular cone face which is positioned more outward in the axial direction as moving toward the ring-like projected part. When the gland packing is to
5 be used while being charged in a stuffing box, therefore, the projected part and the ring-like seal member are easily deformed only by applying a low tightening force in the axial direction, so that the projected part and the ring-like seal member are positioned in a
10 plane substantially perpendicular to the axis of the valve rod or the like, and hence the density of the projected part is increased and a large stress is generated in a radial direction so that the packing is strongly brought into tight contact with the inner face
15 of the stuffing box and the outer peripheral face of a valve rod or the like. This can surely prevent penetration leakage through the projected part from occurring, and enhance sealing properties between the stuffing box and the valve rod. Furthermore, the ring-like projected
20 part has a closely packed folded structure and is very elastic, and hence the ring-like projected part can satisfactorily follow a small amount of wear, thereby ensuring penetration leak prevention and high sealing properties.

25 In the further gland packing of the invention, a

ring-like projected part which is projected outward in the axial direction is formed on at least one end face in an axial direction of a die mold packing part and in at least one of outer and inner end portions in a radial direction, the die mold packing part being configured by windingly laminating an expanded graphite tape into a spiral shape and die-molding the lamination into a ring-like shape, a ring-like seal member is brought into tight contact with the one end face in the axial direction of the die mold packing part excluding the ring-like projected part, the outer face of the ring-like seal member is formed as an oblique circular cone face which is positioned more inward in the axial direction as moving toward the ring-like projected part, and the projection end face of the ring-like projected part is substantially positioned in an extension plane of the oblique circular cone face.

The gland packing may be configured so that ring-like projected parts are respectively outward projected in the axial direction from the both end faces in the axial direction of the die mold packing part and in the outer or inner end portion, or ring-like seal members are respectively brought into tight contact with the end faces in the axial direction of the die mold packing part excluding the ring-like projected parts.

The gland packing is different from the above-mentioned other gland packings only in that the oblique circular cone face constituted by the projection end face of the ring-like projected part and the outer face of the ring-like seal member is formed as a circular cone face of an inverse inclination so that the oblique circular cone face is positioned more inward in the axial direction as moving toward the projected part. According to the gland packing, sure prevention of the penetration leakage and high sealing properties can be exerted by the synergistic effect of the following configurations: the leakage of a pressurized fluid which penetrates into minute gaps formed in windingly laminated parts of the expanded graphite tape constituting the die mold packing part is prevented from occurring by the ring-like seal member; stress relaxation due to the swelling out in the axial direction of the die mold packing part is suppressed by the ring-like seal member; and, when the gland packing is to be used while being charged in a stuffing box, the projected part and the ring-like seal member are easily deformed only by applying a low tightening force in the axial direction, so that the projected part and the ring-like seal member are positioned in a plane substantially perpendicular to the axis of the valve rod

or the like, and hence the density of the projected part is increased and a large stress is generated in a radial direction so that the packing is strongly brought into tight contact with the inner face of the stuffing box and the outer peripheral face of the valve rod or the like, whereby penetration leakage through the projected part is surely prevented from occurring and sealing properties between the stuffing box and the valve rod are enhanced.

As the ring-like seal member in the gland packing of each of the above-mentioned configurations, any one of a lamination of a sheet material having impermeability, a single plate, and metal foil may be selectively used.

15

Brief Description of the Drawings

Fig. 1 is a longitudinal section view of a gland packing of a first embodiment of the invention.

Fig. 2 is a longitudinal section view of a gland packing of a second embodiment of the invention.

Fig. 3 is a longitudinal section view of a gland packing of a third embodiment of the invention.

Fig. 4 is a longitudinal section view of a gland packing of a fourth embodiment of the invention.

Fig. 5 is a longitudinal section view of a gland

packing of a fifth embodiment of the invention.

Fig. 6 is a longitudinal section view of a gland packing of a sixth embodiment of the invention.

Fig. 7 is a longitudinal section view of a gland
5 packing of a seventh embodiment of the invention.

Fig. 8 is a longitudinal section view of a gland packing of an eighth embodiment of the invention.

Fig. 9 is a longitudinal section view of a gland packing of a ninth embodiment of the invention.

10 Fig. 10 is a longitudinal section view of a gland packing of an eleventh embodiment of the invention.

Fig. 11 is a longitudinal section view of a gland packing of a twelfth embodiment of the invention.

Fig. 12 is a longitudinal section view of a gland
15 packing of a thirteenth embodiment of the invention.

Fig. 13 is a longitudinal section view of a gland packing of a fourteenth embodiment of the invention.

Fig. 14 is a longitudinal section view of a gland packing of a fifteenth embodiment of the invention.

20 Fig. 15 is a longitudinal section view of a gland packing of a sixteenth embodiment of the invention.

Fig. 16 is a longitudinal section view of a gland packing of a seventeenth embodiment of the invention.

Fig. 17 is a longitudinal section view of a gland
25 packing of an eighteenth embodiment of the invention.

Fig. 18 is a longitudinal section view showing use example 1 of the gland packings of the embodiments of the invention.

Fig. 19 is a longitudinal section view showing use
5 example 2 of the gland packings of the embodiments of the invention.

Fig. 20 is a longitudinal section view showing use examples 3 to 5 of the gland packings of the embodiments of the invention.

10 Fig. 21 is an enlarged half longitudinal section view illustrating the penetration leakage prevention action in a use state of the gland packing of the second embodiment of the invention.

Fig. 22 is an enlarged half longitudinal section
15 view illustrating the deformation action of a projected part in a use state of the gland packing of the first embodiment of the invention.

Fig. 23 is a table in which stress generating states of the packings of the invention, a prior art
20 packing, and comparison packings are listed.

Fig. 24 is a table showing results of gas-seal tests of use examples 1 to 5 of the gland packing of the invention, and use examples of prior art packings.

Fig. 25 is a half longitudinal section view showing
25 an example of a prior art gland packing.

Fig. 26 is a longitudinal section view showing a use example of the prior art gland packing.

Fig. 27 is a longitudinal section view showing another use example of the prior art gland packing.

5 Fig. 28 is a half longitudinal section view showing another example of a prior art gland packing.

Fig. 29 is a longitudinal section view showing a use example of the gland packing of Fig. 28.

10 Fig. 30 is a half longitudinal section view showing an example of a gland packing which is a comparison example.

Fig. 31 is a half longitudinal section view showing another example of a gland packing which is a comparison example.

15

Best Modes for Carrying Out the Invention

Hereinafter, embodiments of the invention will be described with reference to the drawings.

First embodiment:

20 Fig. 1 is a longitudinal section view of a gland packing G1 of a first embodiment of the invention. In the figure, 1 designates a die mold packing part. The die mold packing part 1 is configured by windingly laminating an expanded graphite tape 1a into a spiral
25 shape, and die-molding the lamination into a ring-like

shape having dimensions of an inner diameter d of 32 mm, an outer diameter D of 48 mm, and a height h of 12 mm. 2 designates a ring-like projected part which is projected outward in an axial direction from one end face in the axial direction of the die mold packing part 1 and in the outer end portion in a radial direction (projection amount $\delta_1 = 2$ mm) and integrally formed, and 3 designates a ring-like projected part which is projected outward in an axial direction (opposite to the ring-like projected part 2) from the other end face in the axial direction of the die mold packing part 1 and in the inner end portion in a radial direction (projection amount $\delta_2 = 2$ mm) and integrally formed. 4 and 5 designate ring-like seal members which are respectively brought into tight contact with the end faces in the axial direction of the die mold packing part 1 excluding the outer and inner ring-like projected parts 2 and 3. The ring-like seal members 4 and 5 are formed by laminating three punched products of an expanded graphite sheet (thickness of 0.38 mm) having impermeability, and the laminated product is compressed together with the die mold packing part 1. As a result, the section shape shown in Fig. 1 is formed. As the expanded graphite tape 1a constituting the die mold packing part 1, a product obtained by

compounding (laminating) knitted meshes of a thin metal wire, or metal foil may be used. The ring-like seal members 4 and 5 may adhere to the die mold packing part 1 so as to be integrated therewith. However, the adhesion of the members is not necessary because the positioning of the members is conducted by the existence of the projected parts 2 and 3.

Second embodiment:

Fig. 2 is a longitudinal section view of a gland packing G2 of a second embodiment of the invention. In the embodiment, a ring-like projected part 2 is projected outward in an axial direction from one end face in the axial direction of a die mold packing part 1 and in the outer end portion in a radial direction, so as to be integrally formed, and a ring-like seal member 4 is brought into tight contact with only one end face in the axial direction of the die mold packing part 1 excluding the ring-like projected part 2. The method of forming the section shape shown in the figure, the configuration of the die mold packing part 1 and the ring-like seal member 4, the dimensions (d, D, h, δ_1) of the parts, etc. are the same as those of the first embodiment, and hence their detailed description is omitted.

Third embodiment:

Fig. 3 is a longitudinal section view of a gland packing G3 of a third embodiment of the invention. In the embodiment, ring-like projected parts 2A and 2B are projected outward in an axial direction from the both end faces in the axial direction of a die mold packing part 1 and in the outer end portion in a radial direction, so as to be integrally formed, and ring-like seal members 4 and 5 are respectively brought into tight contact with the both end faces in the axial direction of the die mold packing part 1 excluding the ring-like projected parts 2A and 2B. The method of forming the section shape shown in the figure, the configuration of the die mold packing part 1 and the ring-like seal members 4 and 5, the dimensions (d, D, h, δ_1 , δ_2) of the parts, etc. are the same as those of the first embodiment, and hence their detailed description is omitted.

Fourth embodiment:

Fig. 4 is a longitudinal section view of a gland packing G4 of a fourth embodiment of the invention. In the embodiment, a ring-like projected part 3 is projected outward in an axial direction from one end face in the axial direction of the die mold packing part 1 and in the inner end portion in a radial direction, so as to be integrally formed, and a ring-like seal member

4 is brought into tight contact with only one end face in the axial direction of the die mold packing part 1 excluding the ring-like projected part 3. The method of forming the section shape shown in the figure, the configuration of the die mold packing part 1 and the ring-like seal member 4, the dimensions (d, D, h, δ_1) of the parts, etc. are the same as those of the first embodiment, and hence their detailed description is omitted.

10 Fifth embodiment:

Fig. 5 is a longitudinal section view of a gland packing G5 of a fifth embodiment of the invention. In the embodiment, ring-like projected parts 3A and 3B are projected outward in an axial direction from the both end faces in the axial direction of a die mold packing part 1 and in the inner end portion in a radial direction, so as to be integrally formed, and ring-like seal members 4 and 5 are respectively brought into tight contact with the both end faces in the axial direction of the die mold packing part 1 excluding the ring-like projected parts 3A and 3B. The method of forming the section shape shown in the figure, the configuration of the die mold packing part 1, the dimensions (d, D, h, δ_1 , δ_2) of the parts, etc. are the same as those of the first embodiment except that punched stainless steel

plates of a thickness of 0.2 mm are used as the ring-like seal members 4 and 5, and hence their detailed description is omitted.

Sixth embodiment:

5 Fig. 6 is a longitudinal section view of a gland packing G6 of a sixth embodiment of the invention. In the figure, 1 designates a die mold packing part. The die mold packing part 1 is configured by windingly laminating an expanded graphite tape 1a into a spiral shape, and die-molding the lamination into a ring-like shape having dimensions of an inner diameter d of 32 mm, an outer diameter D of 48 mm, and a height h of 10 mm. 6 designates a ring-like projected part which is projected outward in an axial direction from one end face in the axial direction of the die mold packing part 1 and in the outer end portion in a radial direction (projection amount $\delta_1 = 0.2$ mm) and integrally formed, and 7 designates a ring-like projected part which is projected outward in an axial direction (opposite to the ring-like projected part 6) from the other end face in the axial direction of the die mold packing part 1 and in the inner end portion in a radial direction (projection amount $\delta_2 = 0.2$ mm) and integrally formed. 8 and 9 designate ring-like seal members which are respectively brought into tight contact with the

10

15

20

25

end faces in the axial direction of the die mold packing part 1 excluding the outer and inner ring-like projected parts 6 and 7. The ring-like seal members 8 and 9 are configured by punched stainless steel plates of a thickness of 0.2 mm so that outer faces 8a and 9a of the members are respectively formed as oblique circular cone faces which have an inclination θ of 15° to a plane perpendicular to the axis so as to be positioned more outward in the axial direction as moving toward the ring-like projected parts 6 and 7, and the projection end faces 6a and 7a of the ring-like projected parts 6 and 7 are respectively substantially positioned in extension planes of the oblique circular cone faces 8a and 9a.

Seventh embodiment:

Fig. 7 is a longitudinal section view of a gland packing G7 of a seventh embodiment of the invention. In the embodiment, a ring-like projected part 6 is projected outward in an axial direction from one end face in the axial direction of a die mold packing part 1 and in the outer end portion in a radial direction, so as to be integrally formed, and a ring-like seal member 8 is brought into tight contact with only one end face in the axial direction of the die mold packing part 1 excluding the ring-like projected part 6. The outer

face 8a of the ring-like seal member 8 is formed as an oblique circular cone face which is positioned more outward in an axial direction as moving toward the ring-like projected part 6. The ring-like seal member 8
5 is formed by laminating three punched products of an expanded graphite sheet (thickness of 0.38 mm) having impermeability, and the laminated product is compressed together with the die mold packing part 1. As a result, the section shape shown in Fig. 7 is formed. The con-
10 figuration of the die mold packing part 1 other than the above, the dimensions (d, D, h, δ 1, θ) of the parts, etc. are the same as those of the sixth embodiment, and hence their detailed description is omitted.

Eighth embodiment:

15 Fig. 8 is a longitudinal section view of a gland packing G8 of an eighth embodiment of the invention. In the embodiment, ring-like projected parts 6A and 6B are projected outward in an axial direction from the both end faces in the axial direction of a die mold packing
20 part 1 and in the outer end portion in a radial direction, so as to be integrally formed, and ring-like seal members 8 and 9 are respectively brought into tight contact with the both end faces in the axial direction of the die mold packing part 1 excluding the ring-like
25 projected parts 6A and 6B. Outer faces 8a and 9a of the

ring-like seal members 8 and 9 are respectively formed as oblique circular cone faces which are positioned more outward in an axial direction as moving toward the ring-like projected parts 6A and 6B. The ring-like seal members 8 and 9 are configured by using a punched polytetrafluoroethylene (PTFE) resin sheet of a thickness of 1.0 mm, and the sheet is compressed together with the die mold packing part 1. As a result, the section shape shown in Fig. 8 is formed. The configuration of the die mold packing part 1 other than the above, the dimensions (d, D, h, δ_1 , δ_2 , θ) of the parts, etc. are the same as those of the sixth embodiment, and hence their detailed description is omitted.

Ninth embodiment:

Fig. 9 is a longitudinal section view of a gland packing G9 of a ninth embodiment of the invention. In the embodiment, a ring-like projected part 7 is projected outward in an axial direction from one end face in the axial direction of a die mold packing part 1 and in the inner end portion in a radial direction, so as to be integrally formed, and a ring-like seal member 8 is brought into tight contact with only one end face in the axial direction of the die mold packing part 1 excluding the ring-like projected part 7. The outer face 8a of the ring-like seal member 8 is formed as an

oblique circular cone face which is positioned more outward in an axial direction as moving toward the ring-like projected part 7. The ring-like seal member 8 is formed by laminating three punched products of an expanded graphite sheet (thickness of 0.38 mm) having impermeability, and the laminated product is compressed together with the die mold packing part 1. As a result, the section shape shown in Fig. 7 is formed. The configuration of the die mold packing part 1 other the above, the dimensions (d, D, h, δ 1, θ) of the parts, etc. are the same as those of the sixth embodiment, and hence their detailed description is omitted.

Tenth embodiment:

A gland packing G10 (see Fig. 9) of a tenth embodiment is strictly the same as the ninth embodiment except that PTFE-impregnated glass fiber fabric is used as the ring-like seal member 8, and hence its illustration and detailed description are omitted.

Eleventh embodiment:

Fig. 10 is a longitudinal section view of a gland packing G11 of an eleventh embodiment of the invention. In the embodiment, among a ring-like projected part 6 which is projected outward in an axial direction from one end face in the axial direction of a die mold packing part 1 and in the outer end portion in a radial

direction and integrally formed, and a ring-like projected part 7 which is projected outward in an axial direction (opposite to the ring-like projected part 6) from the other end face in the axial direction of the die mold packing part 1 and in the inner end portion in a radial direction and integrally formed, the projection end face 6a of the ring-like projected part 6 which is outside in a radial direction is projected outward in the axial direction beyond an oblique circular cone face 8a of one seal member 8 of ring-like seal members 8 and 9 which are brought into tight contact with the both end faces in the axial direction of the die mold packing part 1 so as to be formed as oblique circular cone faces which have an inclination θ of 15° to a plane perpendicular to the axis. The method of forming the section shape shown in the figure, the other configuration, the dimensions of the parts, etc. are the same as those of the sixth embodiment, and hence their detailed description is omitted.

Twelfth embodiment:

Fig. 11 is a longitudinal section view of a gland packing G12 of a twelfth embodiment of the invention. In the embodiment, the projection end face 6a of a ring-like projected part 6 which is projected outward in an axial direction from one end face in the axial

direction of a die mold packing part 1 and in the outer end portion in a radial direction is projected outward in the axial direction beyond an oblique circular cone face 8a of a ring-like seal member 8 which is brought
5 into tight contact on the side of the one end face in the axial direction of the die mold packing part 1 so that the outer face 8a is formed as an oblique circular cone face which is positioned more outward in an axial direction as moving toward the ring-like projected part
10 6. The method of forming the section shape shown in the figure, the other configuration, the dimensions of the parts, etc. are the same as those of the seventh embodiment, and hence their detailed description is omitted.

15 Thirteenth embodiment:

Fig. 12 is a longitudinal section view of a gland packing G13 of a thirteenth embodiment of the invention. In the embodiment, the projection end faces 6a and 6b of ring-like projected parts 6A and 6B which are
20 respectively projected outward in an axial direction from the both end faces in the axial direction of a die mold packing part 1 and in the outer end portions in a radial direction are projected outward in an axial direction beyond oblique circular cone faces 8a and 9a
25 of the ring-like seal members 8 and 9 which are brought

into tight contact with the both end faces in the axial direction of the die mold packing part 1 so that the outer faces 8a and 9a are formed as oblique circular cone faces which are respectively positioned more outward in an axial direction as moving toward the ring-like projected parts 6A and 6B. The method of forming the section shape shown in the figure, the other configuration, the dimensions of the parts, etc. are the same as those of the eighth embodiment, and hence their detailed description is omitted.

Fourteenth embodiment:

Fig. 13 is a longitudinal section view of a gland packing G14 of a fourteenth embodiment of the invention. In the embodiment, the projection end face 7a of the ring-like projected part 7 which is projected outward in an axial direction from one end face in the axial direction of a die mold packing part 1 and in the inner end portion in a radial direction is projected outward in the axial direction beyond an oblique circular cone face 8a which is brought into tight contact on the side of the one end face in the axial direction of the die mold packing part 1 so that the outer face 8a is formed as an oblique circular cone face which is positioned more outward in an axial direction as moving toward the ring-like projected part 7. The method of

forming the section shape shown in the figure, the other configuration, the dimensions of the parts, etc. are the same as those of the ninth embodiment, and hence their detailed description is omitted.

5 Fifteenth embodiment:

Fig. 14 is a longitudinal section view of a gland packing G15 of a fifteenth embodiment of the invention. The embodiment is configured so that the outer faces 8a and 9a of the ring-like projected parts 8 and 9 which
10 are respectively brought into tight contact with the both end faces in the axial direction of a die mold packing part 1 are respectively formed as oblique circular cone faces which have an inclination θ of 15° to a plane perpendicular to the axis so as to be posi-
15 tioned more inward in an axial direction as moving toward the ring-like projected parts 6 and 7, in the opposite manner as the sixth embodiment, and the projection end faces 6a and 7a of the ring-like projected parts 6 and 7 are respectively substantially positioned
20 in extension planes of the oblique circular cone faces 8a and 9a. The method of forming the section shape shown in the figure, the other configuration, the dimensions of the parts, etc. are the same as those of the sixth embodiment, and hence their detailed descrip-
25 tion is omitted.

Sixteenth embodiment:

Fig. 15 is a longitudinal section view of a gland packing G16 of a sixteenth embodiment of the invention. In the embodiment, a ring-like seal member 8 which is brought into tight contact only on the side of one end face in an axial direction of a die mold packing part 1 is formed so that the outer face 8a is formed as an oblique circular cone face which is positioned more inward in an axial direction as moving toward a ring-like projected part 6 in the opposite manner as the seventh embodiment. The method of forming the section shape shown in the figure, the other configuration, the dimensions of the parts, etc. are the same as those of the seventh embodiment, and hence their detailed description is omitted.

Seventeenth embodiment:

Fig. 16 is a longitudinal section view of a gland packing G17 of a seventeenth embodiment of the invention. In the embodiment, ring-like seal members 8 and 9 which are respectively brought into tight contact with the both end faces in an axial direction of a die mold packing part 1 are formed so that the outer faces 8a and 9a are formed as oblique circular cone faces which are positioned more inward in an axial direction as moving toward ring-like projected parts 6A and 6B in

the opposite manner as the eighth embodiment. The method of forming the section shape shown in the figure, the other configuration, the dimensions of the parts, etc. are the same as those of the eighth embodiment, and hence their detailed description is omitted.

Eighteenth embodiment:

Fig. 17 is a longitudinal section view of a gland packing G18 of an eighteenth embodiment of the invention. In the embodiment, a ring-like seal member 8 which is brought into tight contact only on the side of one end face in an axial direction of a die mold packing part 1 is formed so that the outer face 8a is formed as an oblique circular cone face which is positioned more inward in an axial direction as moving toward a ring-like projected part 6 in the opposite manner as the ninth embodiment. The method of forming the section shape shown in the figure, the other configuration, the dimensions of the parts, etc. are the same as those of the ninth embodiment, and hence their detailed description is omitted.

In the gland packings G1 to G18 of the embodiments, as the expanded graphite tape 1a constituting the die mold packing part 1, a product obtained by compounding (laminating) knitted meshes of a thin metal wire, or metal foil may be used. As the ring-like seal

members 4, 5, 8, and 9, any sheet having impermeability may be used. In accordance with various use conditions, for example, the material of the members may be adequately selected from an expanded graphite sheet; a
5 stainless steel plate; and a PTFE sheet; and in addition a film of polyphenylene sulfide (PPS), polyether ether ketone (PEEK), aramid, or the like; a sheet of nitrile-butadiene rubber (NBR), chloroprene rubber (CR), synthetic rubber (SR), fluoro rubber, or the
10 like; and a metal foil or a thin plate of copper, aluminum, lead, inconel, or the like.

The ring-like seal members 4, 5, 8, and 9 may adhere to the die mold packing part 1 so as to be integrated therewith. However, the adhesion of the
15 members is not necessary because the positioning of the members is conducted by the existence of the projected parts 2, 3, 6, and 7.

Typical use manners of the gland packings of the thus configured embodiments will be described.

20 Use example 1:

Fig. 18 shows a use manner in which a plurality of gland packings G2 of the second embodiment and gland packings G4 of the fourth embodiment are alternately arranged in an axial direction on the outer peripheral
25 face of a valve rod or the like 11 in a stuffing box

10, braided packings 12 and 12 are respectively disposed at the both ends in the axial direction of the arrangement, and a tightening force is applied to one end in the axial direction through a packing gland 13, thereby forming a shaft seal part. In the use manner, minute gaps 14 such as shown in Fig. 21 are formed in windingly laminated parts of the expanded graphite tape 1a constituting the die mold packing part 1 of each of the gland packings G2 and G4, and a pressurized fluid penetrates into the minute gaps 14. However, the leakage of the penetrating fluid to the outside is blocked by the ring-like seal member 4 and also stress relaxation due to the swelling out in the axial direction of the die mold packing part 1 is suppressed by the ring-like seal member 4. The ring-like projected part 2 which is projected outward in the axial direction from the die mold packing part 1 is easily deformed by applying a low tightening force in the axial direction, and hence the density of the projected part is increased and a large stress is generated in a radial direction so that the packing is strongly brought into tight contact with the inner face of the stuffing box 10 and the outer peripheral face of the valve rod or the like 11. This surely prevents also the leakage through the projected part 2 from occurring, and en-

hances sealing properties between the stuffing box 10 and the valve rod or the like 11. Furthermore, the ring-like projected part 2 has a closely packed folded structure and is very elastic, and hence can satisfactorily follow a small amount of wear, thereby ensuring penetration leak prevention and high sealing properties.

Use example 2:

Fig. 19 shows a use manner in which a plurality of gland packings G1 of the first embodiment and gland packings 51 of the prior art shown in Fig. 25 are alternately arranged in an axial direction on the outer peripheral face of a valve rod or the like 11 in a stuffing box 10, and a tightening force is applied to one end in the axial direction through a packing gland 13, thereby forming a shaft seal part. In the use manner, even when a pressurized fluid penetrates into the minute gaps 59 such as shown in Fig. 25 formed in windingly laminated parts of the tape-like material 50 constituting the die mold packing part 51, the leakage of the penetrating fluid to the outside is blocked by the ring-like seal members 4 and 5 of the gland packing G1 and also stress relaxation due to the swelling out in the axial direction of the die mold packing part 1 is suppressed by the ring-like seal members 4 and 5.

The ring-like projected parts 2 and 3 which are projected outward in the axial direction from the die mold packing part 1 are easily deformed as shown in Fig. 22 by applying a low tightening force in the axial direction, and hence the density of the projected part is increased and a large stress is generated in a radial direction so that the packing is strongly brought into tight contact with the inner face of the stuffing box 10 and the outer peripheral face of the valve rod or the like 11. In the same manner as use example 1 described above, this surely prevents also the leakage through the projected parts 2 and 3 from occurring, and enhances sealing properties between the stuffing box 10 and the valve rod or the like 11. Furthermore, the ring-like projected parts 2 and 3 have a closely packed folded structure and are very elastic, and hence can satisfactorily follow a small amount of wear, thereby ensuring penetration leak prevention and high sealing properties.

Use example 3:

Fig. 20 shows a use manner in which a plurality of gland packings G7 of embodiment 7 and gland packings G9 or G10 of embodiment 9 or 10 are alternately arranged in an axial direction on the outer peripheral face of a valve rod or the like 11 in a stuffing box 10, and a

tightening force is applied to one end in the axial direction through a packing gland 13, thereby forming a shaft seal part. In the use manner, in the same manner as the use examples described above, the ring-like seal member 8 blocks the leakage of the fluid penetrating into the minute gaps 14 to the outside, and suppresses stress relaxation due to the swelling out in the axial direction of the die mold packing part 1. Furthermore, the ring-like projected parts 6A and 6B and the ring-like seal member 8 are easily deformed by applying a low tightening force in the axial direction so as to be positioned in a plane substantially perpendicular to the axis of the valve rod or the like 11, and hence the density of the projected parts 6A and 6B is increased and a large stress is generated in a radial direction so that the projected parts are strongly brought into tight contact with the inner face of the stuffing box 10 and the outer peripheral face of the valve rod or the like 11. This can surely prevent penetration leakage through the projected parts 6A and 6B from occurring, and maintain sealing properties between the stuffing box 10 and the valve rod or the like 11 at a high level.

Use example 4:

In place of the gland packings G7 and G9 or G10

used in use example 3 shown in Fig. 20, the gland packing G12 of embodiment 12 and the gland packing G14 of embodiment 14 are similarly used so as to form a shaft seal part. Also in the use manner, in the same manner as that described in use example 3, penetration leak prevention and high sealing properties between the stuffing box 10 and the valve rod or the like 11 can be maintained.

Use example 5:

In place of the gland packings G7 and G9 or G10 used in use example 3 shown in Fig. 20, the gland packing G16 of embodiment 16 and the gland packing G18 of embodiment 18 are similarly used so as to form a shaft seal part. Also in the use manner, in the same manner as that described in use examples 3 and 4, penetration leak prevention and high sealing properties between the stuffing box 10 and the valve rod or the like 11 can be maintained.

Fig. 23 is a table showing stress generating states in the case where the gland packing G1 of the first embodiment and the gland packing G6 of the sixth embodiment are used as the gland packing of the invention, a gland packing G01 consisting only of the die mold packing 51 shown in Fig. 25 is used as a prior art packing, gland packings G02 and G03 are used as compar-

ison packings, the gland packing G02 being formed by bringing ring-like seal members 60 and 60 into tight contact with the whole area of the both end faces in the axial direction of the die mold packing 51 as shown in Fig. 30, the gland packing G03 being formed by integrally projecting ring-like projected parts 61 and 62 from the both end faces in the axial direction of the die mold packing 51 and in the outer and inner end portions in a radial direction, and bringing ring-like seal members 63 and 63 of a thickness corresponding to the same height as that of the projected parts 61 and 62 into tight contact with the both end faces in the axial direction of the die mold packing 51 excluding the projected parts 61 and 62, and a constant compression force f is applied in the axial direction to the gland packings. In the figure, the length of each arrow corresponds to the magnitude of the stress.

As seen from Fig. 23, according to the gland packings G1 and G6 of the first and sixth embodiments of the invention, the stresses of the portions corresponding to the ring-like projected parts 2 and 3, and 6 and 7 are very greater than those in the prior art packing and the comparison packings, the performance of preventing a fluid from leaking through the ring-like projected parts 2 and 3, and 6 and 7 is excellent, and

the tight adhesion force against the stuffing box and the outer peripheral face of a valve rod or the like is large so as to exhibit excellent sealing properties.

Fig. 24 is a table showing results of gas-seal tests which were conducted on use examples 1 to 5 of the gland packing of the invention, and the use examples of prior art packings shown in Figs. 27 and 29 under the conditions that nitrogen gas N₂ was filled at 21 Kgf/cm² at ordinary temperature.

As seen from the figure, according to the gland packing of the invention, the leakage amount is very small even in the case where the tightening face pressure is low, thereby exhibiting excellent sealing properties. In a region to which a high tightening face pressure is applied, the leakage amount can be improved to a level of 1/10 to 1/100.

Industrial Applicability

According to the invention, even when a pressurized fluid penetrates into minute gaps formed in windingly laminated parts of an expanded graphite tape constituting the die mold packing part, it is possible to prevent the fluid from leaking, and also to suppress stress relaxation due to the swelling out in an axial direction of the die mold packing part. When the gland

packing is to be used while being charged in a stuffing
box, furthermore, the projected part which is formed on
the die mold packing part so as to be outward projected
in the axial direction can be easily deformed only by
5 applying a low tightening force in the axial direction,
and hence the density of the projected part is in-
creased and a large stress is generated in a radial
direction so that the packing is strongly brought into
tight contact with the inner face of the stuffing box
10 and the outer peripheral face of a valve rod or the
like. This surely prevents penetration leakage through
the projected part from occurring, and the sealing
properties between the stuffing box and the valve rod
can be maintained at a high level. Furthermore, the
15 ring-like projected part has a closely packed folded
structure and is very elastic, and hence the ring-like
projected part can satisfactorily follow a small amount
of wear, thereby attaining an effect that the penetra-
tion leak prevention and high sealing properties can be
20 maintained for a long term.

According to the invention, when the gland packing
is to be used while being charged in a stuffing box,
the ring-like projected part which is formed on the die
25 mold packing part so as to be outward projected in an

axial direction, and the ring-like seal member are easily deformed only by applying a low tightening force in the axial direction, so that the projected part and the seal member are positioned in a plane substantially perpendicular to the axis of the valve rod or the like, and hence the density of the projected part is increased and a large stress is generated in a radial direction so that the projected part and the seal member are strongly brought into tight contact with the inner face of the stuffing box and the outer peripheral face of the valve rod or the like. In the same manner as described above, therefore, the penetration leak prevention and high sealing properties can be maintained for a long term.

According to the invention, in the same manner as the gland packing set forth in claims 4 to 6, a ring-like projected part and ring-like seal member are strongly brought into tight contact with the inner face of a stuffing box and the outer peripheral face of a valve rod or the like, only by applying a low tightening force in an axial direction, whereby the penetration leak prevention and high sealing properties can be ensured maintained for a long term.

CLAIMS

1. A gland packing wherein a ring-like projected part which is projected outward in an axial direction is formed on at least one end face in an axial direction of a die mold packing part and in at least one of
5 outer and inner end portions in a radial direction, said die mold packing part being configured by windingly laminating an expanded graphite tape into a spiral shape and die-molding the lamination into a
10 ring-like shape, a ring-like seal member is brought into tight contact with said one end face in the axial direction of said die mold packing part excluding said ring-like projected part, and said ring-like projected part is projected in the axial direction beyond an
15 outer face of said ring-like seal member.

2. A gland packing according to claim 1, wherein ring-like projected parts are respectively projected outward in the axial direction from the both end faces in the axial direction of said die mold packing part
20 and in the outer or inner end portion in a radial direction, and ring-like seal members are respectively brought into tight contact with said end faces in the axial direction of said die mold packing part excluding said ring-like projected parts.

25 3. A gland packing according to claim 1, wherein

ring-like projected parts are respectively projected outward in the axial direction from one end face in the axial direction of said die mold packing part and in the inner end portion in a radial direction, and the other end face in the axial direction of said die mold packing part and in the outer end portion in a radial direction, and ring-like seal members are respectively brought into tight contact with said end faces in the axial direction of said die mold packing part excluding said ring-like projected parts.

4. A gland packing according wherein a ring-like projected part which is projected outward in an axial direction is formed on at least one end face in an axial direction of a die mold packing part and in at least one of outer and inner end portions in a radial direction, said die mold packing part being configured by windingly laminating an expanded graphite tape into a spiral shape and die-molding the lamination into a ring-like shape, a ring-like seal member is brought into tight contact with said one end face in the axial direction of said die mold packing part excluding said ring-like projected part, the outer face of said ring-like seal member is formed as an oblique circular cone face which is positioned more outward in the axial direction as moving toward said ring-like projected

part, and the projection end face of said ring-like projected part is substantially positioned in an extension plane of said oblique circular cone face.

5 5. A gland packing according to claim 4, wherein
ring-like projected parts are respectively projected outward in the axial direction from the both end faces in the axial direction of said die mold packing part and in the outer or inner end portion in a radial direction, and ring-like seal members are respectively
10 brought into tight contact with said end faces in the axial direction of said die mold packing part excluding said ring-like projected parts.

6. A gland packing according to claim 4, wherein
15 ring-like projected parts are respectively projected outward in the axial direction from one end face in the axial direction of said die mold packing part and in the inner end portion in a radial direction, and also from the other end face in the axial direction of said die mold packing part and in the outer end portion in a
20 radial direction, and ring-like seal members are respectively brought into tight contact with said end faces in the axial direction of said die mold packing part excluding said ring-like projected parts.

7. A gland packing according wherein a ring-like
25 projected part which is projected outward in an axial

direction is formed on at least one end face in an axial direction of a die mold packing part and in at least one of outer and inner end portions in a radial direction, said die mold packing part being configured

5 by windingly laminating an expanded graphite tape into a spiral shape and die-molding the lamination into a ring-like shape, a ring-like seal member is brought into tight contact with said one end face in the axial direction of said die mold packing part excluding said

10 ring-like projected part, the outer face of said ring-like seal member is formed as an oblique circular cone face which is positioned more inward in the axial direction as moving toward said ring-like projected part, and the projection end face of said ring-like

15 projected part is substantially positioned in an extension plane of said oblique circular cone face.

8. A gland packing according to claim 7, wherein ring-like projected parts are respectively projected outward in the axial direction from the both end faces

20 in the axial direction of said die mold packing part and in the outer or inner end portion in a radial direction, and ring-like seal members are respectively brought into tight contact with said end faces in the axial direction of said die mold packing part excluding

25 said ring-like projected parts.


9. A gland packing according to claim 7, wherein
ring-like projected parts respectively projected out-
ward in the axial direction from one end face in the
axial direction of said die mold packing part and in
5 the inner end portion in a radial direction, and also
from the other end face in the axial direction of said
die mold packing part and in the outer end portion in a
radial direction, and ring-like seal members are re-
spectively brought into tight contact with said end
10 faces in the axial direction of said die mold packing
part excluding said ring-like projected parts.

10. A gland packing according to any one of claims
1, 2, 3, 4, 5, 6, 7, 8, and 9, wherein said ring-like
seal member is selected from a lamination of a sheet
15 material having impermeability, a single plate, and
metal foil.

Abstract

The present invention relates to a gland packing which is made of a material configured by windingly laminating an expanded graphite tape into a spiral shape. The gland packing can prevent penetration leakage through minute gaps existing in windingly laminated parts, from occurring, can be sufficiently deformed so as to exhibit sure sealing properties even at a low tightening force, and has following properties against a small amount of wear so as to ensure high sealing properties, so that high sealing performance can be maintained for a long term. In the gland packing, ring-like projected parts 2 and 3 are disposed on end faces of a die mold packing part 1 made of an expanded graphite tape 1a windingly laminated into a spiral shape so as to be integrated with the part. Ring-like seal members 4 and 5 are brought into tight contact with the end faces of the die mold packing part 1 excluding the ring-like projected parts 2 and 3 in such a manner that the ring-like projected parts 2 and 3 are projected in an axial direction beyond the outer faces of the respective ring-like seal members.

Fig.1



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of)	
Takahisa Ueda et al)	Art Unit: 3611
Appln. No. : TBA)	Ex: D. DePumpo
Filed : March 26, 1998)	
For : GLAND PACKING)	

LETTER TO THE OFFICIAL DRAFTSMAN


Honorable Commissioner of Patents and Trademarks
Washington, D.C. 20231

Sir:

Submitted herewith is a tracing of Fig. 1 in red showing
how Fig. 1 and the remaining figures will be cross-hatched.

Respectfully submitted,

By:


Felix J. D'Ambrosio
Reg. No. 25,721

March 26, 1998

JONES, TULLAR & COOPER, P.C.
P.O. Box 2266 Eads Station
Arlington, Virginia 22202
(703) 415-1500

Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8




Fig.9




Fig.10




Fig.11




Fig.12




Fig.13




Fig.14




Fig.15




Fig.17




Fig.18




Fig.19




Fig.20




Fig.21




Fig.22




Fig.23

KINDS		STRESS GENERATED WHEN COMPRESSED
PACKINGS OF THE INVENTION	G 1	
	G 6	
PRIOR ART PACKING	G 0 1	
COMPARISON PACKINGS	G 0 2	
	G 0 3	

10/14

Fig. 24

LEAK AMOUNT	TIGHTENING FACE PRESSURE 100	USE EXAMPLE 1 (FIG. 18)	USE EXAMPLE 2 (FIG. 19)	USE EXAMPLE 3 (FIG. 20)	USE EXAMPLE 4 (FIG. 20)	USE EXAMPLE 5 (FIG. 20)	USE EXAMPLE 6 (FIG. 26)	USE EXAMPLE 7 (FIG. 27)	USE EXAMPLE 8 (FIG. 29)
		0.2	0.1	1.0	0.2	0.5	90	100	60
	TIGHTENING FACE PRESSURE 200	0.05	0.008	0.01	0.05	0.03	1	3	2
	TIGHTENING FACE PRESSURE 300	0.0003	0.01	0.001	0.001	0.01	0.03	0.2	0.1

UNIT: LEAK AMOUNT = cc/min, TIGHTENING FACE PRESSURE = kg/cm²

Fig.25 (




Fig.26




Fig.27




Fig.28




Fig.29




Fig.30





Fig.31



COMBINED DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

This declaration is of the following type:

- ☐ original
- ☐ design
- ☐ supplemental
- ☒ national stage of PCT
- ☐ divisional
- ☐ continuation
- ☐ continuation-in-part (CIP)

My residence, post office address and citizenship are as stated next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed for and for which a patent is sought on the invention entitled:

GLAND PACKING

the specification of which

- ☐ is attached hereto
- ☐ was filed on _____, as
Application Serial No. _____
and was amended on _____
(if applicable)
- ☒ was described and claimed in PCT International application
No. PCT/JP95/00862 filed on May 1, 1995
and as amended under PCT Article 19 on _____
(if any).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any Amendment referred to above.

I acknowledge duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, Sec. 1.56.

- ☐ In compliance with this duty there is attached an information disclosure statement. 37 CFR 1.97.

I hereby claim foreign priority benefits under Title 35, United States Code, Sec. 119, of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent of inventor's certificate having a filing date before that of the application on which priority is claimed:

[] no such applications have been filed
[X] such applications have been filed as follows.

Prior Foreign Application(s)

<u>6-94930</u> (Number)	<u>Japan</u> (Country)	<u>9/5/1994</u> (day/month/year filed)	[X] Yes	[] No
<u> </u> (Number)	<u> </u> (Country)	<u> </u> (day/month/year filed)	[] Yes	[] No

I hereby claim the benefit under Title 35, United States Code, Sec. 120 of any United States application(s) listed below, and insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Sec. 112, I acknowledge the duty to disclose all information known to be material to patentability as defined in Title 37, Code of Federal Regulations, Sec. 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

<u> </u> (Application Serial No.)	<u> </u> (Filing Date)	<u> </u> (patented, pending, abandoned)
<u> </u> (Application Serial No.)	<u> </u> (Filing Date)	<u> </u> (patented, pending, abandoned)

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agents to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

George M. Cooper, Reg. No. 20,201	Eric S. Spector, Reg. No. 22,495
Felix J. D'Ambrosio, Reg. No. 25,721	Douglas R. Hanscom, Reg. No. 26,600
James W. Hellwege, Reg. No. 28,808	William A. Blake, Reg. No. 30,548
	John P. Foryt Reg. No. 32,866

Send correspondence to

Felix J. D'Ambrosio
JONES, TULLAR & COOPER, P.C.
P.O. Box 2266 Eads Station
Arlington, VA 22202

Direct telephone calls

TO:

(703) 415-1500

I hereby declare all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor Takahisa UEDA

Inventor's signature Takahisa Ueda 27/11/1995 (Date)

Residence 5-10, Mukogaoka 4-chome, Sanda-shi, HYOGO 669-13, JAPAN

Citizenship JAPAN

Post Office Address Same as Residence

Full name of second joint inventor, if any Masaru FUJIWARA

Inventor's signature Masaru Fujiwara 27/11/1995 (Date)

Residence 1088-3, Tanigawa, Sannancho, Hikami-gun, HYOGO 669-31, JAPAN

Citizenship JAPAN

Post Office Address Same as Residence

Full name of third joint inventor, if any _____

Inventor's signature _____ (Date)

Residence _____

Citizenship _____

Post Office Address _____

Full name of fourth joint inventor, if any _____

Inventor's signature _____ (Date)

Residence _____

Citizenship _____

Post Office Address _____